

# 2600SERIES



## DELUXE CAB

An optional deluxe cab comes standard with heater and air conditioning, wide opening doors, front window wiper, Bluetooth radio, USB port, and a spacious, comfortable interior.



## TRANSMISSION CHOICES

12 forward and reverse speeds with partial synchromesh (2645), power shuttle (2660 & 2670), or 3-range HST (2638 & 2660). Whatever your transmission preference, there is a 2600 series tractor for you.



## WORK IN COMFORT

All 2600 series tractors come standard with Mahindra's own mComfort seat. Features include extra cushioning for operator relief, mechanical suspension seats, adjustable headrest, and foldable armrests.

## 2600 SERIES ATTACHMENTS

TRACTOR	2638 HST	2638 HST CAB	2645 SHUTTLE	2645 SHUTTLE CAB	2660 HST	2660 HST CAB	2660 PST	2660 PST CAB	2670 PST CAB
<b>LOADER MODEL</b>	<b>2638L</b>	<b>2638CL</b>	<b>2645L</b>	<b>2645CL</b>	<b>2660L</b>	<b>2660CL</b>	<b>2660L</b>	<b>2660CL</b>	<b>2670CL</b>
Standard Bucket Size [in]	66		66				72		78
Maximum Lift Height [in]	101.4		101.9				115.4		115.4
Dig Depth [in]	4.5		4.8				5.2		5.2
Lift Capacity to Full Height at Pivot Pin [lbs]	1634		2041				3122		3122
Breakout Force [lbs]	2696		3430				5225		5225
Shipping Weight [lbs]	985		1177				1270		1318
<b>BACKHOE MODEL</b>		<b>60B</b>					<b>65B</b>		
Standard Bucket Size [in]		16					18		
Maximum Dig Depth [in]		95					112		
Dig Depth 2' Flat Bottom [in]		93.5					110		
Dig Force Bucket [lbs]		3439					3895		
Dig Force Dipper [lbs]		2214					2358		
Shipping Weight [lbs]		1250					1100		



## 2600 SERIES SPECIFICATIONS

TRACTOR	2638 HST	2638 HST CAB	2645 SHUTTLE	2645 SHUTTLE CAB	2660 HST	2660 HST CAB	2660 PST	2660 PST CAB	2670 PST CAB	
<b>ENGINE</b>										
Type	Four-stroke, Naturally Aspirated, Direct Injection, Water Cooled Diesel Engine				Four-stroke, Turbocharged, Direct Injection, Water Cooled Diesel Engine					
Engine HP (kW) @ RPM	37.4 (27.5) @ 2400		44 (33) @ 2600		60 (44.5) @ 2300			70 (52) @ 2300		
Displacement [in <sup>3</sup> (cc)]	166.7 (2732)				161.7 (2650)					
Number of Cylinders	4				3					
Fuel Tank [gal (L)]	9 (34)				16 (60.6)			18.5 (70)		
<b>DRIVE TRAIN</b>										
Transmission	HST - 3 Ranges		Sync, shuttle with part synchromesh		HST - 3 Ranges			Power Shuttle		
Number of Speeds	Infinite		12F / 12R		Infinite			12F / 12R		
Clutch	Damper		Dry, single plate		Damper			Dry Single Plate		
Brakes	Wet Disc Brake, Mechanical									
<b>PTO</b>										
Type	Independent									
Rear PTO RPM	540 @ 2400		540 @ 2650		540 @ 2300					
Mid PTO RPM	2000 @ 2500 (OPT)		N/A		2000 @ 2500 (OPT)			N/A		
PTO HP (kW)	31 (23.2)	29.5 (22)	36 (26.8)		46.3 (34.5)		48.5 (36.2)		53.8 (40.1)	
<b>HYDRAULICS</b>										
Type	Open Center									
Implement Pump Output [gpm (L/min)]	7.6 (28.7)		8.2 (31.0)		11.8 (44.7)					
Maximum Total Flow [gpm (L/min)]	11.7 (44.3)		12.7 (48.1)		16.7 (63.2)					
Standard Rear Valve	N/A				1 Spool					
3-Point Hitch	CAT 1				CAT I with Telescoping Stabilizers & Flex Links			CAT II with Telescoping Stabilizers & Flex Links		
Lift Capacity [lb (kg)]	2646 (1200)				3314 (1503)			3528 (1600)		
<b>ELECTRICAL</b>										
Battery	12 V, 800 CCA				12 V, 925 CCA					
Alternator	12 V, 90 A									
<b>DIMENSIONS</b>										
Overall Length [in (mm)]	119.3 (3030)				138.8 (3525)			144.4 (3667)		
Overall Width [in (mm)]	63.2 (1605)				71.1 (1805)			71.5 (1817)		
Overall Height [in (mm)]	94.4 (2400)				102 (2590)					
Wheelbase [in (mm)]	67.7 (1719)				73.7 (1871)			83 (2100)		
Minimum Ground Clearance [in (mm)]	14.5 (370)				15.7 (400)					
Turning Radius [ft (m)]	N/A									
Weight [lb (kg)]	3130 (1420)	3351 (1520)	3285 (1490)	3506 (1590)	4145 (1884)	4585 (2080)	4145 (1884)	4585 (2080)	5390 (2445)	
<b>WHEELS &amp; TIRES</b>										
AG [Front/Rear]	7-16 6PR / 11.2-24 4PR		8.3 x 16 / 12.4 x 24		9.5x16 6PR / 14.9x24 6PR			9.5 x 20 / 14.9 x 28		
IND [Front/Rear]	10-16.5 / 43 x 16-20				12x16.5 6PR / 16.9x24 8PR			10.5/80 x 18 / 18.4 x 24		
TURF [Front/Rear]	N/A				N/A				LSW305-521 / LSW570-648	