

9000 SERIES



LIFT MORE IN THE FRONT

With a lift capacity of up to 5,415 lbs at 162" high with the 9125CL front loader, the 9000 series possesses the highest loader lift capacity in its class.



AIR SUSPENSION SEAT

9000 series tractors come standard with the mComfort Air Ride seat, featuring adjustable armrests and headrest, to reduce operator fatigue and increase productivity.



EASY MAINTENANCE

The one-piece tilting hood allows for easy access to common service items. Simply unlock via a pulled lever. Servicing your vehicle has never been simpler.

9000 SERIES ATTACHMENTS

TRACTOR	9110 S CAB	9110 P CAB	9125 S CAB	9125 P CAB
LOADER MODEL			9125CL	
Standard Bucket Size [in]			87	
Maximum Lift Height [in]			162	
Dig Depth [in]			6.1	
Lift Capacity to Full Height at Pivot Pin [lbs]			5415	
Breakout Force [lbs]			6874	
Shipping Weight [lbs]			2450	



9000 SERIES SPECIFICATIONS

TRACTOR	9110 S CAB	9110 P CAB	9125 S CAB	9125 P CAB
ENGINE				
Type	Four-stroke, Turbocharged, Direct Injection, Water Cooled Diesel Engine			
Engine HP (kW) @ RPM	110 (82) @ 2300		120 (89.52) @ 2300	
Displacement [in ³ (cc)]	215.4 (3529)			
Number of Cylinders	4			
Bore & Stroke [in]	Bore: 3.78, Stroke: 4.8			
Fuel Tank [gal (L)]	44.9 (170)			
DRIVE TRAIN				
Transmission	Full Synchro Mesh with Forward / Reverse Power Shuttle & Constant Mesh Range			
Number of Speeds	12F / 12R	24F / 24R + 8 Creepers	12F / 12R	24F / 24R + 8 Creepers
Clutch	Wet Clutch			
Brakes	Hydraulic Wet disc			
PTO				
Type	3-speed Independent Single Lever PTO	2-speed Independent Single Lever PTO	3-speed Independent Single Lever PTO	2-speed Independent Single Lever PTO
Rear PTO RPM	540/540E/1000	540/1000	540/540E/1000	540/1000
PTO HP (kW)	93.5 (69.7)		106 (79.1)	
HYDRAULICS				
Type	Open center with Position & Draft Control			
Implement Pump Output [gpm (L/min)]	21.2 (80.25)			
Maximum Total Flow [gpm (L/min)]	30.6 (116)			
3-Point Hitch	CAT II w/ Telescoping Stabilizers, & Flex Links			
Lift Capacity [lb (kg)]	7480 (3392)	9460 (4290)	7480 (3392)	9460 (4290)
ELECTRICAL				
Battery	12 V, 110 Ah 1000 CCA			
Alternator	12 V, 110 A			
DIMENSIONS				
Overall Length [in (mm)]	173.2 (4400)			
Overall Width [in (mm)]	89.1 (2262)		91.3 (2319)	
Overall Height [in (mm)]	115.4 (2930)		116.5 (2960)	
Wheelbase [in (mm)]	100.4 (2550)			
Minimum Ground Clearance [in (mm)]	18.9 (480)		20.1 (510)	
Turning Radius [ft (m)]	13 (3.98)			
Weight [lb (kg)]	9385 (4256)		9535 (4325)	
WHEELS & TIRES				
AG [Front/Rear]	13.6R24 / 16.9R38 Radial		14.9R24 / 18.4R38 Radial	